

Environmentally friendly photosensitive sensor

Product specifications

Customer	
Date	2021.7.16
Model	LS06-B F3
Product number	


Make	
Approval	
Customer Signatures	

Sales center 5109 T3 32
 Address: 32nd Floor,Tower T3,One Excellence,No.5109Menghai Avenue,Nanshan District, Shenzhen, China
 Website www.nysenba.com
 Tel 86-755-82594756 18929323299
 Fax 86-755-82594762

Product function

1. (CdS) ROHS
Replace Photoresistors(Cds),RoHS Compliance/Pb-free/Cd-free.
2. LCD
adjustable m15(a)-3tic(a)allCD4(,mobm)-6iliehon64(e)-3,c(a43(m)-6(e)-3(r)13(a)-3,a)]TJETEMCQq/P #M

Product Dimensions




Note

1. Long foot positive pole Short pin negative
mm , ±0.15mm
Unit: mm± 0.15mm
2. The appearance color of colloid shall be subject to the sample
3. 1.0mm
Protruded resin under the base is 1.0mm maxium.


Ta=25 MAXIMUM RATING (TA = 25 ° C)			
Parameter name	Symbol	Rating	Unit
- Collector-Emitter Voltage	V _{CEO}	20	V
- Emitter-Collector Voltage	V _{ECO}	5	V
Consumption	P _c	70	mW
Working temperature	T _{opr}	-25 85	°C
Storage temperature	T _{stg}	-40 100	°C

■ Ta=25 ELECTOR-OPTICAL CHARACTERISTICS (TA = 25


Typical photoelectric characteristics curves




Change of illuminance and photocurrent



Photowavelength map



Temperature and photocurrent diagram



Temperature and dark current diagram

■ Recommended Soldering Conditions

Mode	Condition
------	-----------

■

Precautions

1.
- 0 +30°C
- 70%
- 3

The storage conditions of the product after leaving the factory shall be 0 to + 30 ° C, the relative humidity shall not be more than 70%, and the storage period shall be 3 months. If the storage period is more than 3 months, the product shall be placed in a closed container with nitrogen or desiccant, and the storage period may be up to one year

2.