

Environmentally friendly photosensitive sensor

Product specifications

Customer	
Date	
Model	LS07-F F3
Product number	

Make	
Approval	
Customer Signatures	

Sales center

5109


T3 32

Address: 32nd Floor, Tower T3, One Excelle

Product function

1. (CdS) [ROHS
Replace Photoresistor (CdS), RoHS Compliance/Pb-free/Cd-free.
2. 8082 E LCD j d
adjust background light automatically, LCD, mobile phone, etc. 100% 5' 0 10 Pf 8y2-v%

Product Dimensions




Note

1. Long pin-Emitter Short pin-Collector
2. Unit: mm 0.15mm
3. The appearance color of colloid shall be subject to the sample
4. Protruded resin under the base is 1.0mm maximum.



Test s

Reference circuit



Typical photoelectric characteristics curves

100


光



Reliability Test

/						
Test Parameter	Reference Criterion	Test Condition	Time	Quantity	Ac/RE	
Resistance to Solder Heat	JESD22-B106	260 °C	10sec	30PCS	0/1	
Thermal Cycle	JESD22-A104	110 °C (15min) 5min 15 °C (15min)	50 cycles	30PCS	0/1	
Thermal Shock	JESD22-A104	520 °C (30s) -40 °C (30s)	50 cycles	30PCS	0/1	

Recommended Soldering Conditions



rsBY€0